www.tamel.pl 985 207 161 CABLE ENTRY 2 LIFTING LUGS DIAGONALLY M10 EXTERNAL OPPOSITE. EARTH POSITION. B 250 74 79 4 HOLES FOR 168 140 311 M20 BOLTS. 406 TAPPED HOLE 381 483 M20x42 DEEP. 60.030 ALL DIMENSIONS IN MILLIMETRES FIRST ANGLE Ø **PROJECTION** NOTE: BROOK 53.0 TERMINAL BOX CAN BE MOUNTED 52.8 (LEFT OR RIGHT) BY REFITTING FEET CROMPTON AND LIFTING LUGS 90° IN APPROPRIATE SECTION THROUGH DIRECTIONS, CABLE ENTRY CAN BE SHAFT EXTENSION SUPPLIED IN ANY ONE OF FOUR (SCALE 1:2.) Produced by **Tamels**, a company of POSITIONS AT 90° INTERVALS.

SHEET NOTE!
SIZE 2.5 END
PROTE
INTENT

NO 1E:
2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST
PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR
INTENTION TO USE RIGID COUPLINGS AND DRIVEN
MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT METRIC
A.C. MOTOR. TOTALLY ENCLOSED FAN VENTILATED.
FRAME SIZE: W-DF250S (2 POLE ONLY.)

	NAME	DATE	Б
DRAWN	JM	08-09-10	\vdash
CHECKED	KC	08-09-10	D
SCALE	1:7		Г

DRG. No. M8706

DRG. REF.

REVISION: | DATE |