

8 HOLES Ø 19 EQUALLY SPACED ON 500 P.C.D. 1 127 250 79 4 HOLES FOR M20 BOLTS. 406 483

NOTE:
TERMINAL BOX CAN BE MOUNTED
(LEFT OR RIGHT) BY REFITTING FEET
AND LIFTING LUGS 90° IN APPROPRIATE
DIRECTIONS. CABLE ENTRY CAN BE
SUPPLIED IN ANY ONE OF FOUR
POSITIONS AT 90° INTERVALS.

TAPPED HOLE
M20x42 DEEP.

53.0
52.8

SECTION THROUGH
SHAFT EXTENSION
(SCALE 1:2.)

ALL DIMENSIONS IN MILLIMETRES



REVISION:

FIRST ANGLE PROJECTION



DATE

Produced by Temels.A. a company of tennion o

SHEET SIZE A 3

NOTE!
2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST
PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR
INTENTION TO USE RIGID COUPLINGS AND DRIVEN
MACHINES WITHOUT ENDPLAY.

TITLE

OUTLINE DIMENSIONS OF STANDARD FOOT/FLANGE MOUNTED METRIC
A.C. MOTOR. TOTALLY ENCLOSED FAN VENTILATED.
FRAME SIZE: W-DF250S-H (2 POLE ONLY.)

			_
	NAME	DATE	ı
DRAWN	JM	01-10-10	H
CHECKED	KC	01-10-10] [
SCALE	1:7		Γ

DRG. No. **M8709**DRG. REF.