
www.tamel.pl 1215 274 191 335 CABLE ENTRY 6 2 LIFTING LUGS M10 EXTERNAL DIAGONALLY EARTH POSITION. OPPOSITE. 640 140 Ø 550.000 549.890 Ø 8 HOLES Ø 24 -EQUALLY SPACED ON 600 P.C.D. 38 29 84 89 4 HOLES FOR M24 BOLTS. 140 216 457 508

NOTE:-TERMINAL BOX CAN BE MOUNTED (LEFT OR RIGHT) BY REFITTING FEET AND LIFTING LUGS 90° IN APPROPRIATE DIRECTIONS. CABLE ENTRY CAN BE SUPPLIED IN ANY ONE OF FOUR POSITIONS AT 90° INTERVALS.

533



597

first angle

ALL DIMENSIONS IN MILLIMETRES



FIRST ANGLE PROJECTION



Produced by **Tamels**. **a**. a company of **Company**

SHEET SIZE A Q

2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDPLAY.

TITLE OUTLINE DIMENSIONS OF STANDARD FOOT/FLANGE MOUNTED METRIC

A.C. MOTOR. TOTALLY ENCLOSED FAN VENTILATED.

FRAME SIZE: W-DF315M-H (2 POLE ONLY.)

l		NAME	DATE	DI
	DRAWN	JM	18-10-10	H
	CHECKED	KC	18-10-10	D
	SCALE	1:9		Г

DRG. No. M9124
DRG. REF.
REVISION: DATE