


NOTE!  
CABLE ENTRY CAN BE SUPPLIED  
IN ANY ONE OF FOUR POSITIONS  
AT 90° INTERVALS.

NOTE!  
STANDARD MACHINES ARE ARRANGED FOR HORIZONTAL OVERHUNG MOUNTING.  
CUSTOMERS SHOULD NOTIFY US WHEN ORDERING IF VERTICAL MOUNTING  
IS REQUIRED. IF VERTICAL, THE MOTOR THRUST BEARING MUST NOT BE  
ALLOWED TO TAKE ANY LOAD OTHER THAN THE WEIGHT OF THE ROTOR  
WITHOUT OUR APPROVAL.

ALL DIMENSIONS IN MILLIMETRES



FIRST ANGLE  
PROJECTION

**BROOK  
CROMPTON**

Produced by **Tamel s.a.** a company of **NTB**  
Technology in Motion

DRG. No. **M8712**

DRG. REF.

REVISION:      DATE

TITLE  
OUTLINE DIMENSIONS OF STANDARD FLANGE MOUNTED METRIC  
A.C. MOTOR. TOTALLY ENCLOSED FAN VENTILATED.  
FRAME SIZE: W-DF250S-D (2 POLE ONLY.)

	NAME	DATE
DRAWN	JM	18-10-10
CHECKED	KC	18-10-10
SCALE	1:7	

SHEET SIZE <b>A3</b>	NOTE! 2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDPLAY.
----------------------------	---