



HOLE TAPPED M10 x22 DEEP TO DIN 332 FORM "D"

A-A  
1:1

TERMINAL BOX POSITION:  
 - CAN BE ARRANGED AT EITHER 9, 12 OR 3 O'CLOCK.  
 - STANDARD TERMINAL BOX POSITION IS 12 O'CLOCK AS SHOWN.  
 CONDUIT ENTRIES:  
 - TERMINAL BOX CAN BE ROTATED AT 90° INTERVALS

ALL MOUNTING DIMENSIONS: ISO 2768-mK ACC TO EN 22768-1/2

ALL DIMENSIONS IN MILLIMETERS



FIRST ANGLE  
PROJECTION

**BROOK  
CROMPTON**

Produced by **Tamel** a company of **ATB**  
ELECTRIC MOTORS Technology in Motion

SHEET SIZE: **A3** TITLE: **OUTLINE DIMENSIONS DRAWING TOTALLY ENCLOSED FAN-COOLED WP-DA100LF FRAME D FLANGE AND FOOT MOUNTED MOTOR.**

DRAWN	NAME	DATE	DRG. No.	WP-DA100LF B35	
CHECKED	SZ	24-04-19	DRG. REF.		
SCALE	RG	24-04-19	REVISION:	DATE	
		1:3			