



HOLE TAPPED M16 x36 DEEP  
TO DIN 332 FORM "D"

A-A  
1:2

TERMINAL BOX POSITION:

- CAN BE ARRANGED AT EITHER 9, 12 OR 3 O'CLOCK.
- STANDARD TERMINAL BOX POSITION IS 12 O'CLOCK AS SHOWN.

CONDUIT ENTRIES:

- TERMINAL BOX CAN BE ROTATED AT 90° INTERVALS

ALL MOUNTING DIMENSIONS: ISO 2768-mK ACC TO EN 22768-1/2

ALL DIMENSIONS IN MILLIMETERS



FIRST ANGLE  
PROJECTION

**BROOK  
CROMPTON**

Produced by **Tamel** a company of **ATB**  
ELECTRIC MOTORS Technology in Motion

SHEET SIZE: **A3**

TITLE: **OUTLINE DIMENSIONS DRAWING TOTALLY ENCLOSED FAN COOLED  
WP-DA180L FRAME D FLANGE AND FOOT MOUNTED MOTOR.**

NAME	DATE	DRG. No.	WP-DA180L B35	
DRAWN	SZ	30-04-19	DRG. REF.	
CHECKED	RG	30-04-19	REVISION:	
SCALE	1:5		DATE	