



TERMINAL BOX POSITION:
 - CAN BE ARRANGED AT EITHER 9, 12 OR 3 O` CLOCK.
 - STANDARD TERMINAL BOX POSITION IS 12 O`CLOCK AS SHOWN.
 CONDUIT ENTRIES
 - TERMINAL BOX CAN BE ROTATED AT 90° INTERVALS

ALL DIMENSIONS IN MILLIMETERS

FIRST ANGLE PROJECTION

BROOK CROMPTON

ALL MOUNTING DIMENSIONS: ISO 2768-mK ACC TO EN 22768-1/2 Produced by *Tamel s.r.l.* a company of **NTB** Technology in Motion

| | | | | | | | | |
|-------------------------|--------|--|--|---------|-----------|----------------------|-------|--|
| SHEET SIZE A3 | TITLE: | OUTLINE DIMENSION DRAWING TOTALLY ENCLOSED FAN COOLED WP-DA160L FRAME C FLANGE AND FOOT MOUNTED MOTOR | | | DRG. No. | WP-DA160L B34 | | |
| | | | | | DRG. REF. | | | |
| | | | | | REVISION: | | DATE: | |
| | | | | | SCALE | 1:3 | | |
| | | | | DRAWN | SZ | 30-04-19 | | |
| | | | | CHECKED | RG | 30-04-19 | | |